



Product Features

- for temperature controlled operation of the KHS HS2® hygiene-flushing box
- to be connected to KHS HS2® hygiene-flushing box
- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- male union thread
- free from dead spots

Standards and Approvals

- according to accepted materials list from German environmental agency
- DIN EN 60751
- ÚA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical Data

- pressure rating PN 16
- max. operating temperature 105 °C
- length of connection cable 5 m

part no.	DN	A1	A2	A3	H1 (mm)	L1 (mm)	L2 (mm)	kg
6890001500	15	G 3/4	G 3/4	G 1/4	65	65	60	0,488
6890002000	20	G 1	G 1	G 1/4	68	67	60	0,549
6890002500	25	G 1 1/4	G 1 1/4	G 1/4	70,5	72	70	0,702
6890003200	32	G 1 1/2	G 1 1/2	G 1/4	78	77	80	0,772
6890004000	40	G 1 3/4	G 1 3/4	G 1/4	79	82	80	0,871
6890005000	50	G 2 3/8	G 2 3/8	G 1/4	88,5	90	80	1,294

accessory

insulation shell for MULTI T-PIECE, figure 471 28
 gunmetal solder union connector, figure 476 04
 gunmetal union connector, union nut, FPT, figure 476 06
 gunmetal union connector, union nut, FPT, with drain valve, figure 476 07
 gunmetal union connector, union nut, MPT, figure 476 08
 solder / pressfit union connector, figure 476 14
 pressfit union connector, MAPRESS stainless steel and copper, figure 476 22
 pressfit union connector, SANPRESS and PROFIPRESS, figure 476 30
 pressfit union connector, SANHA and NiroSan, figure 476 35
 pressfit union connector, MEPLA, figure 476 40
 pressfit union connector, MAPRESS stainless steel, figure 476 20
 pressfit union connector, SANPRESS INOX, figure 476 70
 pressfit union connector for Viega RAXOFIX, figure 476 32